MEDIACAST VIEWER



MODEL: DS67U

MediaCAST Viewer is a small form-factor, set-top box designed to receive media content over the IP network for display on LCDs, projectors and televisions.

OVERVIEW.

MediaCAST Viewers deliver digital signage and automated visual communications. The high-performance ruggedized hardware supports a full spectrum of industry-standard streaming video and audio as well as other digital media formats. They support video resolutions through 1080 HD. The Viewers are industrial grade high-reliability embedded computers utilizing SSD's and a fanless design for 24 x 7 x 365 always-on applications.

Viewers support scheduled playback through MediaCAST Kiosk Central $^{\text{TM}}$. This enables content to be pushed out in the form of playlists, all-call broadcasts and emergency mode messages.

Viewers can be used to accept scheduled video and audio broadcasts from MediaCAST Master Controller to classroom displays and for distance learning applications.



MediaCAST Viewers playback and decode a full-range of media formats. They are software upgradable to support new formats providing a longer usable life.

Video- Mpeg 4, H.264/AVC,

Audio- MP3

Live video/audio- Multicast & unicast live streaming

Documents- Adobe PDF, Microsoft Word, Microsoft Excel, Google Docs, Text docs



Presentations- PowerPoint, Google Slides

Images- JPG, GIF, PNG and more

Web Sites – Html / (Http, Https)

Viewers support output to LCDs, projectors and televisions through DisplayPort and HDMI. The small form-factor boxes can be installed on a wall and hidden behind an LCD screen or on a shelf with a ceiling-mount projector. To automate turning on/off displays they provide control of connected displays through RS-232 compatible with most brands of industry-standard a/v equipment.

MediaCAST Viewers are used for digital signage in entryways, hallways, media centers, conference rooms and common areas. They can be used in classrooms and offices when a computer is not available for access to IPTV, media on-demand and to push out automated messages and announcements.





MediaCAST Viewers combined with MediaCAST Kiosk Central provides a robust, enterprise-wide, digital signage and visual communication system.

Optional Accessories SKUs:

MCAST-VIEWER-CAB-HDMI VIEWER-PROG-1 MCAST-VIEWER-IR

SPECIFICATIONS.

Hardware

Ruggedized steel chassis Intel Celeron 3855U Dual-Core 1.6 GHz CPU Integrated Intel HD 510 Graphics (Dual Display) 120GB 2.5" SATA III 6Gbps SSD

4 GB 1600 MHz DDR3L SODIMM RAM

Windows Embedded 7 (64-bit)

Intel i219 Ethernet (Dual 10/100/1000 Mbps RJ45 LAN interfaces IEEE 802.3u 100 Base-T rev 1.0)

Realtek RTL8821 AE WLAN 802.11 b/g/n/ac and BT

1 x RS232/RS422/RS485 COM Port

1 x RS232 COM Port

4 x USB 2.0

2 x USB 3.0

1 x DisplayPort (to 1920x1080)

1 x HDMI (to 1920x1080)

Realtek ALC662 HD Audio (1/8" stereo jacks: mic in / line out)

Kensington lock option

Operating Temperature Range:

 $0 - 40 \, ^{\circ}\text{C}$ [1] 10 - 90% RH (non-condensing)

[1] Follow mounting Guidelines

Dimensions/Weight

200(L) x 165(W) x 39.5(H) mm, 1.3L, 2 kg

Power

AC Power adapter (brick) 65W Input: AC 100-240v (1.7 m AC cable) Output: 19v/4.47A DC (1.7 m DC cable)

Mount

Stand (metal feet) Standard VESA Mounting Bracket (75 / 100 mm) Wall-mount bracket